

SAFETY DATA SHEET

1. Identification

Product identifier

Natural Gasoline

Other means of identification

SDS number

005-GHS

Synonyms

Gasoline, Casing Head Gasoline
See section 16 for complete information.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Fire-fighting
equipment/instructions**

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
------------	------	-------

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*
	0.4 mg/l	2,5-Hexanedi - on, without hydrolysis		*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1

Flammability limit - upper (%) 8

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density < 3 Estimated

Relative density

Components	Species	Test Results
Hydrogen sulfide (CAS 7783-06-4)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 0.38 mg/l, 960 Minutes
09-66-0 (CAS 7783-06-4)		
Acute		
Acute		
<i>Inhalation</i>	Rat	
<i>Inhalation</i>		
LC50	Rat	

Components

Species

Test Results

SARA 302 Extremely hazardous substance

Chemical name CAS number

Country(s) or region

Inventory name

On inventory (yes/no)*